



SAE x SAE Full Coupling

Model AWC Series

- AISI-1018 steel
- Maximum operating temperature 400°F
- 9/16"-18 to 2 1/2"-12 port sizes
- Compatible with most hydraulic fluids & lubricating oils



Options

- Optional stainless steel (Consult Factory)



Dimensional Detail

Model Number	D Ports		A	B	C
AWC-4-4	7/16"-20 x 7/16"-20	in	.91	0.38	1.02
		mm	23.1	9.65	26.0
AWC-6-6	9/16"-18 x 9/16"-18	in	1	0.51	1.25
		mm	25.4	12.90	31.75
AWC-8-8	3/4"-16 x 3/4"-16	in	1.25	0.69	1.63
		mm	31.75	17.53	41.40
AWC-10-10	7/8"-14 x 7/8"-14	in	1.38	0.81	1.79
		mm	35.05	20.57	45.5
AWC-12-12	1 1/16"-12 x 1 1/16"-12	in	1.5	0.98	2.06
		mm	38.1	24.92	52.32
AWC-14-14	1 5/16"-12 x 1 5/16"	in	1.63	1.10	2.06
		mm	41.40	27.94	52.32
AWC-16-16	1 5/16"-12 x 1 5/16"	in	1.75	1.23	2.06
		mm	44.45	31.24	52.32
AWC-20-20	1 5/8"-12 x 1 5/8"-12	in	2.25	1.54	2.06
		mm	57.15	39.22	52.32
AWC-24-24	1 7/8"-12 x 1 7/8"-12	in	2.75	1.79	2.2
		mm	69.85	45.55	55.88
AWC-32-32	2 1/2"-12 x 2 1/2"-12	in	3.25	2.419	2.5
		mm	82.55	61.44	63.5



AWC - 12-12 -

Series	Series & Thread Style
AWC	SAE

Code	Material
Omit	Steel
*SS	304 Stainless Steel

**Consult factory for availability*

Port Size	Port THREAD
4-4	7/16"-20
6-6	9/16"-18
8-8	3/4"-16
10-10	7/8"-14
12-12	1 1/16"-12
14-14	1 3/16"-12
16-16	1 5/16"-12
20-20	1 5/8"-12
24-24	1 7/8"-12
32-32	2 1/2 "-12