



Press Fit Sight Windows SLP

Specifications

- Trogamid T sight window / Buna 70 durometer o-ring
 - Minimum wall thickness reservoir is 5.0 mm
 - Hole cutout in tank $\pm .01$ mm diameter of window
 - Maximum temperature 212°F (100°C) degrees / Red level indicator point
- Press fit oil level indicators are designed for tanks and reservoirs with a wall thickness 5.0 mm or greater wall thickness. It has excellent sealing capability with ribs and a 70 durometer o-ring in a close tolerance to cutout hole.
- The SLP has a red dot indicator located on front of lens and white reflector for an accurate view of the oil level. These press fit oil windows can be removed and cleaned if required.

The SLP oil windows are produced from Trogamid T, which gives the SLP window mechanical strength and compatibility with oil, gasoline, fuel, and most solvents. They can be used on gearboxes, and hydraulic reservoirs, or lube reservoirs.



SLP

Dimensional Detail

Model	Hole Diameter		d	D	h1	h2
SLP-17	17 \pm 0.1 MM	in	0.7	0.7	0.1	0.3
		mm	16.9	18	3	7
SLP-20	20 \pm 0.1 MM	in	0.8	0.9	0.2	0.4
		mm	19.6	24	4	10
SLP-26	26 \pm 0.1 MM	in	1.0	1.2	0.2	.45
		mm	25	30	4	11.5
SLP-32	32 \pm 0.1 MM	in	1.2	1.4	0.2	0.5
		mm	31.7	36	4	13
SLP-38	38 \pm 0.1 MM	in	1.5	1.7	0.2	0.6
		mm	37.5	42	4	14
SLP-40	40 \pm 0.1 MM	in	1.6	1.7	0.2	0.6
		mm	39.5	44	4	14

See website technical bulletin TB.TA12.708 for further information at Technical Data - www.lenzinc.com.

