



Domed Oil Sights

- Transparent polymide material / not compatible with alcohol
- Maximum operating temperature 194°F (90°C) / nitrile seal, fiber seal FASIT 202
- Compatible with petroleum based fluids, gasoline, fuel, and variety of solvents
- NPT and BSP threads available
- Maximum pressure 44 PSI (3 Bar)





LSD-16

LSD-8

LSD-32
LSD-48LSDF-32
LSDF-48

LSD-12NPT



Dimensional Detail

NPT Model	METRIC BSPP Model	F Port		CH	D	d	h1	h2 BSPP	h2 NPT	Torque FT-LB/NM
LSDN-6	LSD-6	3/8"	in.	0.7	0.9	0.43	0.6	0.4	0.4	6"
			mm	19	22	11	16	10	10	8
LSDN-8	LSD-8	1/2"	in.	0.9	1.1	0.6	0.7	0.4	0.52	9"
			mm	24	28	16	17	10	13.3	12
LSDN-12	LSD-12	3/4"	in.	1.2	1.4	1.0	0.8	0.4	0.54	12"
			mm	30	35	25	20	10	13.8	16
LSDN-16	LSD-16	1"	in.	1.6	1.7	0.9	0.9	0.4	0.7	12"
			mm	40	42	23	24	10.5	17.3	16
	LSD-32	2"	in.			2.3	1.3	1.3	N/A	12"
			mm			59	32	32		16
	LSD-48	3"	in.			3.3	2.5	1.3	N/A	12"
			mm			85	63	32		16
	LSD-M20	M20 x 1, 5	IN	0.9	1.1	0.8	0.7	0.4		4.5-6
			MM	24	28	20	18	10		(6-8)

See website technical bulletin TB.TA12.708 for further information at (Technical Data - www.lenzinc.com).

LSDF-32 2" BSP Weld Flange
LSDF-48 3" BSP Weld Flange